




2480-▲-DST



Submitted Model No.: \_\_\_\_\_

Specific Features: \_\_\_\_\_



▲ Designate proper finish suffix



## KITCHEN FAUCETS

- Pilar® Series
- Two Handle Widespread Deck Mount
- 3 or 4 Hole Sink Applications
- Quick Snap® Hose Installation

### STANDARD SPECIFICATIONS:

- 3/8" O.D. straight, staggered pex supply tubes - 33" (838 mm) long.
- 10 1/2" (267 mm) long, 13" (330 mm) high spout swings 180°.
- 1/4" turn stops.
- Control mechanism is a diamond coated ceramic cartridge.
- Hose length (veggie spray) 45" (1143 mm).
- Maximum flow rate of 1.8 gpm @ 60 PSI.
- Maximum mounting deck thickness of 2 1/2".


### WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes; or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.



### COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- Indicates compliance to ICC/ANSI A117.1
- Verified compliant with .25% weighted average Pb content regulations.



Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or [www.deltafaucet.com](http://www.deltafaucet.com) for finish options and product availability.

DSP-K-2480-DST Rev. C



55 E. 111th Street, Indianapolis, Indiana 46280  
350 South Edgeware Road, St. Thomas, ON N5P 4L1  
© 2013 Masco Corporation of Indiana