

Your Delta Faucet handshower incorporates a backflow protection system that has been tested to be in compliance with ASME A112.18.3 and ASME A112.18.1/CSA B125.1. It incorporates two certified check valves in series, which operate independently and are integral, non-serviceable parts of the wand assembly.

## Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.specselect.com for finish options and product availability.

# **O**DELTA

### WALL BAR HAND HELD SHOWERS

- Certified Dual Check Valves
- Decorative Wall Bar

#### STANDARD SPECIFICATIONS:

- ABS hand held shower with two settings.
- 69" ultraflex hose: 57011.
- 70" ultraflex hose: 51521, 51551.
- 60-82" stretchable hose: 51501, 51502.
- Certified dual check valves for backflow protection.
- Decorative wall bar.
- 2.5 gpm @ 80 psi (9.5 L/min @ 552 kPa).
- ADA compliance applies to the hand shower and hose only: 51551-WH.

#### **WARRANTY**

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes: or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.



#### COMPLIES WITH:

■ ASME A112.18.1/CSA B125.1 ◆


#### **Spray Patterns**





Full Body Spray

Pause





55 E. 111th Street, Indianapolis, Indiana 46280 350 South Edgeware Road, St. Thomas, ON N5P 4L1 © 2012 Masco Corporation of Indiana