

Features


- Metal construction
- Metal throatplate
- One-piece, self-contained ceramic disc valve allows both volume and temperature control
- Temperature memory allows faucet to be turned on and off at any temperature setting
- High-temperature limit stop for added safety
- Vandal-resistant aerator
- 2 gallons (7.5 L) per minute
- Lower flow aerator options are available (refer to the Kohler Price Book)
- Grid drain with tailpiece
- Vandal-resistant lever handles and aerator
- For 4" (10.2 cm) centers
- 4-1/4" (10.8 cm) spout


Codes/Standards Applicable

Specified model meets or exceeds the following:

- ASME A112.18.1/CSA B125.1
- IAPMO/UPC
- NSF 61
- Energy Policy Act of 1992 (EPACT)
- ADA

Specified Model





K-15598

ADA

LAVATORY FAUCET



Colors/Finishes

CP: Polished Chrome

Model	Description	Colors/Finishes
K-15598-F	Lavatory faucet with 4-1/2" (11.4 cm) lever handle and flexible connections	CP
K-15598-P	Lavatory faucet with 4-1/2" (11.4 cm) lever handle and ground joint connections	CP
K-15598-F5	Lavatory faucet with 5-3/4" (14.6 cm) lever handle and flexible connections	CP
K-15598-5P	Lavatory faucet with 5-3/4" (14.6 cm) lever handle and ground joint connections	CP

Product Specification

Single-control centerset lavatory faucet shall be of metal construction. Valve shall be a one-piece, self-contained, ceramic disc valve, allowing volume and temperature control. Valve shall feature temperature memory, allowing the faucet to be turned on and off at any temperature setting. Valve shall include a high-temperature limit stop. Faucet shall be rated at 2.0 gallons (7.5 L) per minute. Faucet shall have lower flow aerator options. Faucet shall include 4" (10.2 cm) centers, 4-1/4" (10.8 cm) spout, vandal-resistant (VR) 4-1/2" (11.4 cm) or 5-3/4" (14.6 cm) lever handle, grid drain with tailpiece, metal throatplate, and VR aerator. Faucet shall be available with either flexible or ground joint connections. Faucet shall be Kohler Model K-15598-_____-CP.



Installation Notes

Install this product according to the installation guide.

