

# KOHLER®

## Roughing-In

# K-3393

## SAN RAPHAEL™

### COMFORT HEIGHT™ POWER LITE® TOILET

### Product Information

Applicable product:	
Elongated bowl toilet	K-3393
ADA compliant (when installed following installation notes).	<b>ADA</b>
Fixture:	
Configuration	one-piece, elongated
Water per flush	1 gal (3.8 L) / 1.4 gal (5.3 L)
Passageway	2-1/8" (5.4 cm)
Water depth from rim	5-7/8" (14.9 cm)
Water area	12" (30.5 cm) x 10" (25.4 cm)
Seat post hole centers	5-1/2" (14 cm)
Pump	2 Hp, 120 V, 8.5 A, 60 Hz
Minimum static pressure required	15 psi (103.4 kPa)

Included components:	
Tank cover	1055954
Bolt cap accessory pack	1013092
Toilet seat	74917
Twin Touch™ dual flush selector	81996
Tank accessory pack	84301
Pump	84153

### Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Receptacle	120 V, 15 A, 60 Hz

### Installation Notes

Install this product according to the installation guide.

Will comply with the American Disabilities Act (ADA) when installed per the requirements of the Accessibility Guidelines, Section 604 Water Closets, of the Act, which include the installation of an open front seat.

Section 604 states the required height of the toilet is 17" (43.2 cm) to 19" (48.3 cm) from the floor to the top of the seat to meet ADA requirements.

Fixture dimensions are nominal and conform to tolerances in ASME Standard A112.19.2.

