

Features

- Digital clock
- 3-year warranty
- 20 minute safety shut-off
- Easy-to-install digital control panel with quick connect cord and connector
- Adjustable time and temperature settings
- Aromatherapy reservoir on steam head

Codes/Standards Applicable


Specified model meets or exceeds the following:

- UL 499

STEAM GENERATOR CONTROL KIT

K-1647-PC

ALSO K-1663, K-1698



Colors/Finishes

- CP: Polished Chrome
- Other: Refer to Price Book for additional colors/finishes

Accessories

- NA: None applicable

Specified Model

Model	Description	Colors/Finishes	
K-1647-PC	Fast-Response® steam control kit with Power Clean™ (shown)	<input type="checkbox"/> CP	<input type="checkbox"/> Other _____
K-1663	Steam generator control kit	<input type="checkbox"/> CP	<input type="checkbox"/> Other _____
K-1698	Fast-Response steam control kit with Power Clean, and 2 steamheads	<input type="checkbox"/> CP	<input type="checkbox"/> Other _____

Required Accessories

For K-1647-PC Fast-Response steam control kit with Power Clean choose one of the following steam generators

K-1695	Fast-Response 5 kW steam generator	<input type="checkbox"/> NA
K-1696	Fast-Response 13 kW steam generator	<input type="checkbox"/> NA
K-1708	Fast-Response 7 kW steam generator	<input type="checkbox"/> NA
K-1713	Fast-Response 15 kW steam generator	<input type="checkbox"/> NA
K-1733	Fast-Response 9 kW steam generator	<input type="checkbox"/> NA
K-1734	Fast-Response 11 kW steam generator	<input type="checkbox"/> NA

Product Specification

The steam generator control kit shall include an easy-to-install digital control panel with quick connect cord and connector. Product shall have adjustable time and temperature settings. Product shall include a digital clock, 20 minute safety shut-off, and aromatherapy reservoir on steam head. Product shall have a quick connect RJ-12 cord and connector. Product shall include a 3 year warranty. Steam generator control kit shall be Kohler Model K-_____-_____.




Required Accessories <i>Continued from previous page.</i>		
For K-1663 steam generator control kit choose one of the following steam generators		
K-1652	5 kW steam generator	<input type="checkbox"/> NA
K-1657	7 kW steam generator	<input type="checkbox"/> NA
K-1658	9 kW steam generator	<input type="checkbox"/> NA
K-1659	11 kW steam generator	<input type="checkbox"/> NA
For K-1698 Fast-Response® steam control kit with Power Clean™ and 2 steamheads choose one of the following steam generators		
K-1697	Fast-Response 26 kW steam generator	<input type="checkbox"/> NA
K-1714	Fast-Response 18 kW steam generator	<input type="checkbox"/> NA
K-1715	Fast-Response 22 kW steam generator	<input type="checkbox"/> NA
K-1716	Fast-Response 30 kW steam generator	<input type="checkbox"/> NA

Installation Notes

Install this product according to the installation guide.



WARNING: Risk of personal injury. Do not install the User Interface Control outside the steam enclosure. The User Interface must be installed within the enclosure to allow the sensors to regulate the temperature and control the flow of steam.



Product Diagram