

KOHLER®

Roughing-In

K-3997
WELLWORTH®
CLASS FIVE® TOILET

Product Information

| | |
|---|-----------|
| Applicable product: | |
| Class Five toilet – left-hand trip lever (shown) | K-3997 |
| Class Five toilet – right-hand trip lever | K-3997-RA |
| Class Five toilet – right-hand trip lever, Insuliner® and tank cover locks | K-3997-RZ |
| Class Five toilet – left-hand trip lever, tank cover locks | K-3997-T |
| Class Five toilet – right-hand trip lever, tank cover locks | K-3997-TR |
| Class Five toilet – left-hand trip lever, Insuliner tank | K-3997-U |
| Class Five toilet – right-hand trip lever, Insuliner tank | K-3997-UR |
| Class Five toilet – left-hand trip lever, Insuliner tank and tank cover locks | K-3997-UT |

| | |
|------------------------|------------------------------------|
| Fixture: | |
| Configuration | two-piece, round-front |
| Water per flush | 1.28 gpf (4.8 lpf) |
| Passageway | 2-1/8" (54 mm) |
| Water area | 10-1/2" (267 mm) x 7-3/4" (197 mm) |
| Water depth from rim | 5-1/4" (133 mm) |
| Seat post hole centers | 5-1/2" (140 mm) |

| | |
|-------------------------|---------|
| Included components: | |
| Bowl | K-4197 |
| Tank | K-4467 |
| Tank cover | 1138565 |
| Trip lever | K-9379 |
| Bolt cap accessory pack | 1013092 |

Installation Notes

Install this product according to the installation guide.

For back-to-back toilet installations: Use only a 45° double wye fitting.

Fixture conforms to ASME standard A112.19.2/CSA B45.1. All dimensions are nominal.

