

Product Information

Applicable product*:	
Bath and shower valve trim	K-T14776-4
Shower trim only – with diverter button	K-T14777-4
Shower trim only – without diverter button	K-T14778-4
Mixing valve trim– with diverter button	K-T14779-4
Mixing valve trim– without diverter button	K-T14780-4
Bath spout	K-14795
Lever handle is ADA compliant. ADA	

Required accessories:	
Rite-Temp® pressure-balancing valve – less stops	K-304-K/CX/PX/UX
Rite-Temp® pressure-balancing valve with stops	K-304-KS/CS/KP/PS/US
Push-button diverter – less stops	K-305-K*
Push-button diverter – with stops	K-305-KS*
HiFlow Rite-Temp® valve with stops	K-306-KS**
Push-button diverter – less stops	K-11748-K
Push-button diverter – with stops	K-11748-KS
* Requires 1016453-C/F diverter button kit.	
** Requires 88526-C/F for thin wall installations.	

Optional accessories:

Thin wall installation kit for K-306 HiFlow Rite-Temp valve	88526
Diverter button kit for K-305 Rite-Temp valve	1016453
Deep rough-in kit for Rite-Temp valve	1111613

Installation Notes

Install this product according to the installation guide.

NOTICE: For K-305 valve: The diverter button kit (1016453-C/F) is required.

NOTICE: For K-306-KS valve: The thin wall installation kit (88526-C/F) is required for thin wall (fiberglass or acrylic) installations.

Avoid cross-flow conditions. Do not install a shut-off device on either valve outlet.

Cap the shower outlet if the deck-mounted spout, diverter, or handshower is connected to the spout outlet.

Install straight pipe or tube drop of 7" (17.8 cm) to 18" (45.7 cm) with single elbow between the valve and the wall-mount spout.

