

Product Information

| | |
|--|----------------------------------|
| Applicable product: | |
| Elongated bowl | K-4325 |
| Elongated bowl with bedpan lugs | K-4325-L |
| ADA and TAS compliant when installed following installation notes. ADA TAS | |
| Fixture: | |
| Configuration | top spud, elongated |
| Water per flush | 1.28 gal (4.85 L)* |
| Spud size | 1-1/2" |
| Passageway | 2-1/8" (5.4 cm) |
| Water area | 10-1/2" (26.7 cm) x 9" (22.9 cm) |
| Water depth from rim | 5-1/4" (13.3 cm) |
| Seat post hole centers | 5-1/2" (14 cm) |
| * Designed to flush with 1.28 gal (4.8 L) of water when installed with a 1.28 gal (4.8 L) flush valve. | |
| Included components: | |
| Spud | 18357 |
| Flush valve requirements: Refer to manufacturer and local codes. | |

Installation Notes

Install this product according to the installation guide.

Will comply with the American Disabilities Act (ADA) when installed per the requirements of the Accessibility Guidelines, Section 604 Water Closets, of the Act. The Model Plumbing Codes require the installation of elongated open-front toilet seats in public bathrooms.

For TAS compliance the required seating height with the toilet seat installed is:

Adults – 17" (43.2 cm) to 19" (48.3 cm)

Children (Elementary Grade Levels 6 through 8 or 9) – 15" (38.1 cm) to 17" (43.2 cm)

