

### Product Information

Applicable product:	
Toilet	K-4323
Toilet – with bedpan lugs	K-4323-L
ADA compliant when installed following installation notes.	<b>ADA</b>
Fixture:	
Configuration	rear spud, elongated
Water per flush	1.28 gallons (4.85 L)*
Spud size	1-1/2"
Passageway	2-1/8" (5.4 cm)
Water area	10-1/2" (26.7 cm) x 9" (22.9 cm)
Water depth from rim	5-1/4" (13.3 cm)
Seat post hole centers	5-1/2" (14 cm)
* Designed to flush with 1.28 gallons (4.85 L) of water when installed with a 1.28 gallon (4.85 L) flush valve. Refer to manufacturer and local codes for flush valve requirements.	
Included components:	
Spud	18357

Recommended accessories:	
1.28 gpf (4.85 lpf) Touchless™ DC toilet flushometer	K-10956
Stronghold™ open-front elongated seat	K-4731-C
Stronghold open-front elongated seat with integrated handle	K-4731-SC
Stronghold Quiet Close™ open-front elongated seat	K-4731-GC

### Installation Notes

Install this product according to the installation guide.

Will comply with the American Disabilities Act (ADA) when installed per the requirements of the Accessibility Guidelines, Section 604 Water Closets, of the Act. In addition, the installation of an elongated open-front seat is required.

The Plumbing Codes require open-front elongated toilet seats on public use toilets.

