




double bend Spouts	Model Number	Reach	Height to Aerator	Overall Height
	S0000	6"	2.000"	4.325"
	S0001	6"	3.750"	7.375"
	S0002	6"	5.000"	9.125"
	S0003	6"	5.750"	9.750"
	S0004	6"	8.500"	12.750"
	S0006*	8"	0.750"	3.500"
	S0007	8"	6.000"	9.750"
	S0009	10"	5.750"	9.750"
	S0010*	12"	0.500"	3.125"
	S0011	12"	6.000"	9.750"
	S0012	18"	3.750"	7.750"

GOOSENECK SPOUTS	Model Number	Reach	Height to Aerator	Overall Height
	S0020	3-5/8"	6.250"	8.750"
	S0030	5-1/4"	5.500"	10.000"
	S0050	8"	6.125"	11.375"
	S0060	8"	10.000"	12.000"
	S0070	9-1/2"	6.500"	9.175"

VACUUM BREAKER SPOUTS	Model Number	Reach	Height to Aerator	Overall Height
	SV003	6"	5.750"	10.500"
	SV006	8"	0.500"	4.000"
	SV010	12"	0.500"	4.000"

All spouts come with a friction washer for rigid spout mounting.
 All spouts have a flow rate of 2.2gpm (8.3L/min) Max
 *Caution: Not recommended for use with model 8133

CRITICAL DIMENSIONS

(DO NOT SCALE)