



615 South Street Garden City, NY 11530 Tel:516-515-5000 Fax:516-515-5050 www.waclighting.com

CATALOG NUMBER	<u>TYPE</u>
PROJECT	

## **DUORAIL™ – SURFACE MOUNT TRANSFORMER**







Ordering Matrix				
Model	Part Number	Finish		
LM2-EN12	500M	DB	СН	BN

Ordering Example (model number - part number - finish): LM2-EN12-500M-BN

## **Product Details**

**Description:** Surface mount magnetic low voltage transformer for the WAC

Duorail™ system. The canopy style enclosure includes the

transformer and the track power feed adaptors.

Catalog LM2 = Low voltage Duorail™

**Number:** EN12 = 12 volt, enclosed canopy transformer

500M = 500 watt magnetic

**Input:** 120V (60Hz)

Output: 12V

Max Load: 500W (2 x 250W circuits)

Max Input Amp: 2X2.5A (@ 120V)

**Mounting:** Installs to a standard junction box. Total weight = 25 lbs.

The standard LM2-EN12 configuration matches the height of

the 8 1/16" standoffs (LM2-X8).

Finish: Available in Dark Bronze (DB), Chrome (CH), and Brushed

Nickel (BN).

Listing: UL & CUL Listed.

5 year WAC Lighting product warranty.

## **Specification Features**

- The LM2-EN12-500M model has two 250w feeds .
- Dims with magnetic low voltage dimmers.
- The output circuit breakers located on the upper lip of the canopy enclosure are a magnetic push to reset type.
- Contains integral de-buzzing coil.
- The surface mount canopy transformer is an ideal choice when the installation is on an existing ceiling.