


HR-2LED-R09D-A

2" Tesla™ New Construction Housing

120V – Non-IC – Airtight

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Non-IC, airtight remodel housing.
For use with HR-2LED series trims.

FEATURES

- Cutout: 3 7/8"
- 120VAC 50/60Hz input
- Non-IC
- Airtight
- May be dimmed to 1% with electronic low voltage (ELV) dimmer
- Provided with push-in wire connector for easy installation
- Accommodates ceiling thickness from 1/2"-1"
- UL and CUL Listed
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Housing and junction box are 20 gauge steel.

J-Box: Three knockouts and three Romex® style wiring connectors provided for ease of installation. Rated for branch wiring.

Driver: Electronic driver, 120VAC 50/60Hz input, 14.3W output. Power factor >0.9. Dimming with thermal protection.

Mounting: Two heavy gauge inner retention clips push out onto ceiling or other mounting surface to firmly hold housing in place. Accommodates surface from 1/2"-1" thick. 3 7/8" cutout hole.

Dimming: May be dimmed to 1% with electronic low voltage (ELV) dimmer. Approved dimmers: Lutron Skylark SELV-300P-WH and Leviton Vizia VPE04.

Rating: Non-IC: insulation must be kept at least 3" away from the housing.

Standards: UL & CUL Listed.

ORDER NUMBER

HR-2LED-R09D-A

COMPATIBLE TRIMS

Model #	Description	Beam	Color Temp	Finish
HR-2LD-ET109	Round, Open Reflector Downlight – Energy Star	16.5° (S), 30° (N), 53° (F)	2700K (27), 3000K (W) 3500K (35), 4000K (C)	Brushed Nickel (BN) Copper Bronze (CB) White (WT)
HR-2LED-T109	Round, Open Reflector Downlight	15° (S), 26° (N), 45° (F)		
HR-2LED-T209	Round, Shower Light	26° (N)		
HR-2LED-T709	Square, Open Reflector Downlight	15° (S), 26° (N), 45° (F)		

Example: **HR-2LED-T109S-27-BN**

See individual trim spec sheets for complete information.

WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050

Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760

Phone (800) 526.2588 • Fax (800) 526.2585