

SPECIFICATION SHEET

LOW VOLTAGE WALL SCONCE

MODEL WS-MR61







Catalog Information							
Model	Description	Lamp/Max Watt	Voltage		Finishes		
WS-MR61	Metal round style	JC-50/50W*	120V to 12V	СН	PT	SB	

*Included with Socket Set

Finish Key: CH = Chrome, PT= Platinum, SB-Satin Brass

Product Features

Description: Low voltage wall sconce. With round metal front fascia. Includes a self-contained electronic transformer. Fits all WAC G600 series glass shades.

1. **Lamp:** Uses a 12 volt, 50 watt bi pin-Halogen lamp with

G6.35 base (supplied). Retained by a screw on frosted bulb shield

- 2. **Transformer:** Electronic 60 watt transformer. Built in auto reset short and overload protection. "Soft start" delayed start extends lamp life.
- 3. **Dimming:** Dimmable with electronic dimmer or generally dimmable with a standard incandescent dimmer (High Frequency output is compatible with most standard dimmers).
- 4. **Mounting:** Installs to a standard 4" junction box. The shade is retained by the socket assembly. Socket attaches to fixture by means of a quick connect jack.

Shades

G613 Cased glass	: AM, BL, GR, RD, WT, YW		
G611 Cased glass	: AM, BL, GR, RD, WT, YW		
G612 Fluted cased	: BL, WT		
G615 Multi color glass	: BG, RP,YP		
G614 Multi color glass	: BG, MF, YR,		

Color Key :

AM=Amber, BL=Blue, RD=Red, WT=White, YW=Yellow BG=Blue/Green, RP=Red/Purple, RW=Red/White, YP=Yellow/Purple, MF=Milifiore, YR=Yellow/Red.

Material

Brass, with plated or painted finish, ceramic bi pin socket.

Listings

UL, CUL Listed.

W.A.C. reserves the right to change details that do not affect overall function and performance.



615 South Street, Garden City, NY 11530 Tel: (516) 515-5000 Fax: (516) 515-5050 168 Brea Canyon Road, City of Industry, CA 91789 Tel: (909) 468-1848 Fax: (909) 468-9958