



Catalog Information

Model	Description	Length	Width	Height	Finishes
HT2	2' foot single circuit track section	23¾"	1 3/8"	¾"	Black, White
HT4	4' foot single circuit track section	47¼"	1 3/8"	¾"	Black, White
HT6	6' foot single circuit track section	71"	1 3/8"	¾"	Black, White
HT8	8' foot single circuit track section	94½"	1 3/8"	¾"	Black, White

Product Features

- Track:** Single Circuit, 3-Wire style
- Supplied:** Two end caps, & mounting hardware
- Capacity:** 20 amps rated, 120V.
- De-rating:** It is common practice to use tracks at 80% capacity to insure compatibility with dimmers, connectors, and existing wiring (1920W maximum).
- Mount:** Can be installed on drywall, or suspended ceilings.
- Cut:** Track may be cut in field.

Options / Accessories

Track may be suspended from flat, sloped ceilings. Use SK suspension kits (specify SK18, SK24, SK36, SK48, available in Black or White). For sloped ceilings, order SK14 adapter. Suspension rods may be field cut without retaping by using SK05 adapters, sold in pairs.

Material

Aluminum extrusion with copper bus wire.

Listing

UL, CUL Listed, New York City Approved

W.A.C. reserves the right to change details that do not affect overall function and performance.

