

**Catalog Information**

2-WIRE (L)	3-WIRE (H)	WIDE 2-WIRE (J)	FINISHES
------------	------------	-----------------	----------



LTK-775	HTK-775	JTK-775	BK, WT, BN/BK, BN/WT
---------	---------	---------	----------------------

Finish Key: BK-Black, WT-White, BN/BK-Black with Brushed Nickel Head, BN/WT-White with Brushed Nickel Head

**Product Features**

- Aiming:** 90° degrees from vertical and 356° rotational.
- Compatible:** L, H, and J models in addition to fitting our own tracks are retrofittable to other manufacturers original tracks (consult factory for specific brand names).
- Special Application:** The J style head may be installed on any "J" style 2-circuit track with the addition of the J-CLIP.
- Lamping:** Re-lamps from the front.
- Socket:** Porcelain with Nickel-plated shell.

Lamp Type	Wattage	Voltage
PAR 38	45W – 150W	120V

**Options/Accessories**

Extensions available for "H" style 3-wire series track heads only. Available in 18", 24", 36" and 48" lengths. Specify H18, H24, H36 or H48 (in BK or WT).

**Material**

Die Cast Aluminum

**Listing**

UL, CUL Listed, New York City Approved.


W.A.C. reserves the right to change details that do not affect overall function and performance.



**SPECIFICATION SHEET**

**LINE VOLTAGE TRACK HEADS**

**MODEL 775**



**Key** In Feet  
**D** Distance To Fixture From Wall Or Floor  
**FC** Initial Footcandle Level At Center Of Beam  
**L** Beam Length (where candlepower drops to 50% of maximum)  
**W** Beam Width (where candlepower drops to 50% of maximum)  
**CBCP** Center Beam Candle Power

Lamp Beam Spread	CBCP	0° Aiming Angle				30° Aiming Angle				45° Aiming Angle				60° Aiming Angle			
		D	FC	L	W	D	FC	L	W	D	FC	L	W	D	FC	L	W
50W PAR38 SP10°	14000	3'	1556	0.5'	0.5'	3'	1010	0.7'	0.6'	3'	550	1.1'	0.7'	3'	194	2.1'	1.0'
		5'	560	0.9'	0.9'	5'	364	1.2'	1.0'	5'	198	1.8'	1.2'	5'	70	3.6'	1.7'
		7'	286	1.2'	1.2'	7'	186	1.6'	1.4'	7'	101	2.5'	1.7'	7'	36	5.0'	2.4'
		9'	173	1.6'	1.6'	9'	112	2.1'	1.8'	9'	61	3.2'	2.2'	9'	22	6.4'	3.1'
50W PAR38 FL25°	3000	3'	333	1.3'	1.3'	3'	217	1.8'	1.5'	3'	118	2.8'	1.9'	3'	42	6.2'	2.7'
		5'	120	2.2'	2.2'	5'	78	3.0'	2.6'	5'	42	4.7'	3.1'	5'	15	10.4'	4.4'
		7'	61	3.1'	3.1'	7'	40	4.2'	3.6'	7'	22	6.5'	4.4'	7'	8	14.6'	6.2'
		9'	37	4.0'	4.0'	9'	24	5.4'	4.6'	9'	13	8.4'	5.6'	9'	5	18.7'	8.0'
75W PAR38 FL25°	4000	3'	444	1.3'	1.3'	3'	289	1.8'	1.5'	3'	157	2.8'	1.9'	3'	56	6.2'	2.7'
		5'	160	2.2'	2.2'	5'	104	3.0'	2.6'	5'	57	4.7'	3.1'	5'	20	10.4'	4.4'
		7'	82	3.1'	3.1'	7'	53	4.2'	3.6'	7'	29	6.5'	4.4'	7'	10	14.6'	6.2'
		9'	49	4.0'	4.0'	9'	32	5.4'	4.6'	9'	17	8.4'	5.6'	9'	6	18.7'	8.0'
90W PAR38 SP10°	16000	3'	1778	0.5'	0.5'	3'	1155	0.7'	0.6'	3'	629	1.1'	0.7'	3'	222	2.1'	1.0'
		5'	640	0.9'	0.9'	5'	416	1.2'	1.0'	5'	226	1.8'	1.2'	5'	80	3.6'	1.7'
		7'	327	1.2'	1.2'	7'	212	1.6'	1.4'	7'	115	2.5'	1.7'	7'	41	5.0'	2.4'
		9'	198	1.6'	1.6'	9'	128	2.1'	1.8'	9'	70	3.2'	2.2'	9'	25	6.4'	3.1'
90W PAR38 FL25°	4100	3'	456	1.3'	1.3'	3'	296	1.8'	1.5'	3'	161	2.8'	1.9'	3'	57	6.2'	2.7'
		5'	164	2.2'	2.2'	5'	107	3.0'	2.6'	5'	58	4.7'	3.1'	5'	21	10.4'	4.4'
		7'	84	3.1'	3.1'	7'	54	4.2'	3.6'	7'	30	6.5'	4.4'	7'	10	14.6'	6.2'
		9'	51	4.0'	4.0'	9'	33	5.4'	4.6'	9'	18	8.4'	5.6'	9'	6	18.7'	8.0'

Data based on GE PAR38 Lamps.  
 PAR38 lamps are not sold by W.A.C Lighting