

SHOWER SYSTEMS MULTIFUNCTIONAL SHOWERHEADS

Model #	Description	Finishes	Roughing-In Dimensions
1660.115	"TREVI" DELUXE ADJUSTABLE SHOWERHEAD Self Cleaning: Flexible ring with spray holes prevents lime scale build up. Spray Pattern: Variable spray adjusts from a conventional spray to an aerated flow to a massage action. Adjustable Showerhead: Showerhead position is adjustable 30° in any direction. 2.5 gpm/9.5L/min. flow restrictor.	.002 Polished Chrome .068 Blackened Bronze (PVD) .099 Polished Brass (PVD) .295 Satin Nickel (PVD)	1/2" NPT FEMALE 100mm (6-7/8)
1660.722	MASSAGE SHOWERHEAD Variable Spray Adjusts from a conventional spray to an aerated flow to a massage action 2.5 gpm/9.5L/min. flow restrictor. SHOWERHEAD ONLY 2.5 gpm/9.5L/min. flow restrictor.	.002 Polished Chrome .008 Polished Nickel .068 Blackened Bronze (PVD) .295 Satin Nickel (PVD)	32mm (1-1/4) DIA. HOLE
1660.701	 "3" FUNCTION SHOWERHEAD Variable Spray Adjusts from a conventional spray to an aerated flow to a massage action 2.5 gpm/9.5L/min. flow restrictor. SHOWERHEAD ONLY 2.5 gpm/9.5L/min. flow restrictor. 	.002 Polished Chrome .068 Blackened Bronze (PVD) .295 Satin Nickel (PVD)	32mm (1-1/4) DIA. HOLE



Style That Works Better

SHOWER SYSTEMS RAIN SHOWER ARMS

Model #	Description	Finishes	Roughing-In Dimensions
1660.190	12" CEILING MOUNT SHOWER ARM • Brass construction • 1/2" NPT Thread	.002 Polished Chrome .008 Polished Nickel .068 Blackened Bronze (PVD) .099 Polished Brass (PVD) .295 Satin Nickel (PVD)	1/2" NPT 21mm DIA. (7/8) 300mm (11-3/4)
1660.194	12" WALL MOUNT RIGHT ANGLE SHOWER ARM • Brass construction • 1/2" NPT Thread	.002 Polished Chrome .008 Polished Nickel .068 Blackened Bronze (PVD) .099 Polished Brass (PVD) .295 Satin Nickel (PVD)	300mm (11-3/4) 65mm (2-1/2) 4 65mm (2-1/2) 1/2" NPT
1660.198	12" WALL MOUNT SHEPHERD'S CROOK SHOWER ARM • Brass construction • 1/2" NPT Thread	.002 Polished Chrome .008 Polished Nickel .068 Blackened Bronze (PVD) .099 Polished Brass (PVD) .295 Satin Nickel (PVD)	1/2" NPT 120mm (4-3/4) 1/2" NPT 320mm (12-5/8)