

Capri Series CF2022/2032/2054/2072

Project

-,--

Approved By

Location

Fixture Type

Quantity

Catalog Number

Features

Shallow euro styled ceiling or wall mount fixture available in three diameters and can be used in various applications including corridors and baths. Fixture mounts to standard junction box (not included).

Construction

Housing is spun 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Interior housing is finished in lighting grade white baked gloss enamel paint. Exposed exterior ring is available in two finish options, white or brushed nickel.

Diffuser

Diffuser is .070" thick injection molded smooth white acrylic that is held in place by a lift and shift motion and secured with three spring clips.

Electrical

This unit is wired with UL listed electronic normal power factor ballast for 120V/60 Hz AC operation.

Lamping

Circline lamps are included with this fixture series. Color temperature is 3000K. 12" fixture includes 1/22 watt, 16" includes 1/32 watt or 1/22 and 1/32 (54 watts) and the 20" includes 1/32 and 1/40 watt circline lamp(s).

Certification

All fixtures are cULus listed for damp locations.

Options

120-277V HPF 13, 18 and 26 watt CFQ lamping options Custom finishes ENERGY STAR qualified

Specifications and dimensions subject to change without notice.

Ordering Information:

Model No.	Lamps			Dimensions		
120V	Finish	Qty	Туре	D	DIA 1	DIA 2
CF2022ET	White	1	FC8T9 22W	4"	10-1/2"	14"
CF2032ET	White	1	FC12T9 32W	4"	13-1/4"	17"
CF2054ET	White	2	(1) FC8T9 22W & (1) FC12T9 32W	4"	13-1/4"	17"
CF2072ET		2	(1) FC12T9 32W & (1) FC16T9 40W	4"	17"	21"
120V	Finish	Qty	Туре	D	DIA 1	DIA 2
CF2022BNET	Brushed Nickel	1	FC8T9 22W	4"	10-1/2"	14"
CF2032BNET	Brushed Nickel	1	FC12T9 32W	4"	13-1/4"	17"
CF2054BNET	Brushed Nickel	2	(1) FC8T9 22W & (1) FC12T9 32W	4"	13-1/4"	17"
CF2072BNET	Brushed Nickel	2	(1) FC12T9 32W & (1) FC16T9 40W	4"	17"	21"



Date

