

# Decorative Nickel Cloud CN232/2U3/432

#### Features

Molded drop dish white acrylic diffuser with distinctive nickel trim ceiling mount fixture is available in three sizes, 12-1/8" x 49-3/4", 17-5/8"x 50" and 25-7/8" x 25-7/8". It can be used in various applications including corridors, kitchens and public spaces. This product offers a flush to ceiling frame and is retained to the fixture body with a clip on one end and screw on the other. The diffuser is captive in the frame. Fixture mounts to standard junction box (not included).

# Construction

Housing is die-formed of 22-gauge steel. Standard mounting holes are included. Decorative frame assembly is constructed of an extruded polymer with a brushed nickel Mylar finish. The entire frame attaches to the housing with a preinstalled bracket on one end and a #8 screw through the other end. Power supply connections can be made inside the fixture wire way or in a junction box (not included).

#### Finish

Back plate is finished lighting grade white baked gloss enamel paint. Frame exterior is brushed nickel Mylar.

#### Diffuser

Acrylic diffuser is .080" thick smooth white.

#### Electrical

This unit can be ordered in the following options: with UL listed instant-start, electronic normal power factor ballast; 120V 60Hz AC (R8 suffix), 120-277 Universal 50/60Hz AC (MV suffix).

#### Lamping

For use with 2/32 or 4/32 watt T8 linear fluorescent lamps or 2/32 watt T8 U lamps with 6" spacing; supplied by others.

# Certification

All fixtures are cULus listed for damp locations.

# **Options (consult factory)**

120-277V HPF ENERGY STAR qualified Dimming

Specifications and dimensions subject to change without notice.



# **Ordering Information:**

Model No.			Lamp	Lamps		ions	Mounting	
Finish	120V	120-277V	Qty	Lamp	Н	W	L	Μ
Satin Nickel	CN232R8	CN232MV	2	F32T8	3-1/2"	12-1/2"	50"	43-3/4"
Satin Nickel	CN2U3R8	CN2U3MV	2	FB32T8	3-1/2"	25-7/8"	25-7/8"	21"
Satin Nickel	CN432R8	CN432MV	4	F32T8	3-1/2"	17-5/8"	50"	43-3/4"

Fixture Type
Quantity

Date

Approved By

Project

Location

Catalog Number

