

# WINCO INC

A Division of **DTT** Dyna Technology Inc

## W6010DE (Diesel) Industrial Portable Generator



The redesigned **W6010DE** now boasts the 10.5 HP HATZ B40, 462cc diesel engine. This engine satisfies the EPA Tier II emissions requirements, runs quieter, smoother, and maintains excellent fuel economy.

Producing 6000 watts of peak power and 5500 watts of continuous power, the seven (7) gallon fuel tank keeps this diesel generator running for over 10 hours at full-load.

With the addition of a 30 amp, 120/240 volt outlet to the receptacle panel there is now more power versatility to meet your power requirements.

Switchless Full Power is standard on this model, allowing the full rated output of the unit from a single 120 volt or 240 volt outlet, or a combination of both simultaneously without the hassle of adjusting voltage settings.

BCI Group U1 12 volt, 235cca battery **not** included

**Options Available:**

- 2-wheel Industrial Dolly Kit
- 4-wheel Industrial Dolly Kit
- Generator Cover
- Single-point Lifting bar
- Plug-in Line Voltage Monitor
- 30 amp (NEMA L14-30P) Locking Plug
- Manual Emergency Transfer/Service Kit

The construction and service industries demand reliable power in a variety of conditions. From roofing contractors to home builders and commercial services providers, WINCO has the portable industrial generator to meet your needs.

All WINCO industrial generators are designed to endure the harsh environments their toughest customers will ultimately place them in. From the baking heat and humidity in Florida to the frigid winters in the northern states, WINCO generators have been proven reliable, easily serviced, and capable of furnishing the power output required of them.

WINCO has established a commitment to ensure that the best generator products are available reflecting quality in workmanship, dependability, and performance. When you need portable power, WINCO has a generator to serve you.

<b>ELECTRICAL SPECIFICATIONS</b>	
Maximum Power Rating	6000 watts
Continuous Power Rating	5500 watts
AC Output Voltage	120/240 volts
Continuous Current Rating	45.8/22.9 amps
Motor Starting Ability	3 hp
120 Volt Full Power	45.8 amps
Generator Type	R.F.L.
<b>ENGINE DATA</b>	
Make/Model	HATZ B40
Displacement	462 cc
Rated Power (3600 rpm)	10.5 hp
Low Oil Protection	Standard
Starting System	Electric
Fuel Tank Capacity	7 gallons
Running Time-Full Load	10 hours
Running Time-Half Load	20 hours
Hour Meter	Standard
<b>120 VOLT RECEPTACLES</b>	
Straight Blade (NEMA 5-20R)	2-20 amp GFCI
Straight Blade (NEMA 5-50R)	1-50 amp
<b>240 VOLT RECEPTACLES</b>	
Twist-Lock (NEMA L6-30R)	1-30 amp
<b>120/240 VOLT RECEPTACLES</b>	
Twist-Lock (NEMA L14-30R)	1-30 amp
<b>SIZE &amp; WEIGHT</b>	
Dimensions (LxWxH)	32x22x23 in.
Shipping Weight	292 lbs.
<b>WARRANTY INFORMATION</b>	
Generator/Engine	2 yrs/2 yrs-2000 hrs.

# WINCO INC

A Division of **DTT** Dyna Technology Inc

225 South Cordova Avenue  
Le Center, MN 56057 USA  
East Coast Sales: (800) 733-2112  
West Coast & Canada: (800) 324-8174  
E-Mail: [wincosales@wincogen.com](mailto:wincosales@wincogen.com)  
Web Site: [www.wincogen.com](http://www.wincogen.com)