

Description: Low RPM, low noise, ceiling mount bathroom fan engineered for continuous operation •Suitable for new construction, or remodeling • HVI certified • ENERGY STAR qualified • UL/cUL listed for use in insulated ceilings (Type I.C.).

Motor/Blower: Permanently lubricated enclosed condenser motor engineered for continuous operation; power rating 120v/60Hz; motor equipped with thermal shut off.

Housing: Rust proof paint on steel body; 4" duct connector with built-in back draft dampener; easy installation antivibration brackets included; designed for installation in ceilings with minimum of 8" clearance.

Grille: Low maintenance, wipe clean; attaches to housing with torsion springs

with torsion springs

Ventilating Area: For bathrooms up to 80 sq ft.

Installation: Complete installation instructions included

Shipping Weight: 15 lbs

Warranty: 6 Years

Architect's Specifications: Ventilation fan will be ceiling mount, ENERGY STAR qualified, with no less than 80 CFM and no more than 0.3 Sones as certified by HVI at 0.1 static pressure in inches water gauge. Power consumption shall be no greater than 22.9 watts and ENERGY STAR rated with an efficiency rating of no less than 3.5 CFM/watt. The motor will be permanently lubricated, engineered for continuous operation. Duct diameter will be 4" round. Fan shall be UL/cUL listed for tub/shower enclosure when used with GFCI branch circuit wiring and shall be UL/CUL listed for use in insulated ceiling (Type I.C.). Fan shall be ASHRAE 62.2, LEED, California Title 24, and Washington VIAQ compliant.










Specifications

SBF 80 G1 Series

Super Quiet Bathroom Ventilation Fan



UL/CUL Listed for installation over tub/shower enclosure when used with GFCI circuit wiring



G1 Grille

Model: SBF 80 G1 Series	4"]	4" Duct	
Static Pressure (inches w.g.)	0.1	0.25	
Air Volume (CFM)	80	64	
Noise (sones)	<0.3	n/a	
Power Consumption (Watts)	22.9	22.0	
Energy Efficiency (CFM/Watts)	3.5	2.9	
Speed (RPM)	817	1009	
Current (AMPS)	0.16	0.16	
ENERGY STAR rated	Y	Yes	
Grille Dimensions	11 5/6"	11 5/6" x 11 5/6"	

Model	Qty	Comments	Project	
			Location	
			Architect	
			Engineer	
			Contractor	
			Submitted by	
			Date	