

Gourmet® Undermount Single Bowl Sink Model ELU2816 and ELUH2816 Series

GENERAL

Highest quality sink formed of #18 (1.2mm) gauge, type 304 (18-8) nickel bearing stainless steel. Undermount.

DESIGN FEATURES

Bowl Depth: 7-1/2" (191mm) (ELU[H]2816), 10" (254mm) (ELU[H]281610), 11-1/2" (292mm) (ELU[H]281612).

Coved Corners: 1-3/4" (44mm) vertical and horizontal radius. Finish: Exposed surfaces are hand blended to a Lustrous

Satin finish.

Underside: Fully protected by heavy duty Sound Guard® undercoating to dampen sound and reduce condensation.

OTHER

Drain Opening: 3-1/2" (89mm).

Note: All Elkay undermount sinks are designed to affix to the underside of any solid surface countertop.

Sinks comply with ASME A112.19.3-08/CSA B45.4-08.

UPC .

These sinks are listed by the International Association of Plumbing and Mechanical Officials as meeting the requirements of the Uniform Plumbing Code.

OPTIONAL ACCESSORIES

Bottom Grid: LKWOBG2816SS


Cutting Boards: CB1713, CBS1316 (ELUH models only)

Drain: LK99

Rinsing Baskets: LKWRB2816SS, LKWERBSS Utensil Caddy for Rinsing Baskets: LKWUCSS Mounting Hardware: LKUCLIP8 (2 packages required)

SINK PACKAGE(S)

MODEL	SINK	BOTTOM GRID	QTY	DRAIN	QTY
ELU2816DBG	ELU2816	LKWOBG2816SS	1	LK99	1
ELU281610DBG	ELU281610	LKWOBG2816SS	1	LK99	1
ELU281612DBG	ELU281612	LKWOBG2816SS	1	LK99	1
ELUH2816DBG	ELUH2816	LKWOBG2816SS	1	LK99	1
ELUH281610DBG	ELUH281610	LKWOBG2816SS	1	LK99	1
ELUH281612DBG	ELUH281612	LKWOBG2816SS	1	LK99	1





Installation Profile of ELU and ELUH Single Bowl Models
The template provided with each sink provides the only type of installation recommended by Elkay.

COUNTERTOP 1/2" (13mm) Reveal (ELUH Sink) COUNTERTOP 1/2" SILICONE CAULK (NOT FURNISHED) FASTENER (NOT FURNISHED) FASTENER (NOT FURNISHED) FASTENER (NOT FURNISHED)

1/8"(3mm)Overhang (ELU Sink) COUNTERTOP SILICONE CAULK (NOT FURNISHED) FASTENER (NOT FURNISHED) FASTENER (NOT FURNISHED) 1-3/8"±1/4" 1/8" OVERHANG

SEE OTHER SIDE FOR PRODUCT DIMENSIONS.

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkayusa.com for most current version of Elkay product specification sheets.

This specification describes an Elkay product with design, quality and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.



SINK DIMENSIONS*

Model Number	Ove L	erall W	Ins L	ide Each B W	owl D	Cutout in Countertop	Minimum Cabinet Size
ELU2816	29 ¹ / ₂ (749mm)		28 (711mm)	16 (406mm)	7 ¹ / ₂ (191mm)		33 (838mm)
ELU281610	29 ¹ / ₂ (749mm)	17 ¹ / ₂ (445mm)	28 (711mm)	16 (406mm)	10 (254mm)		33 (838mm)
ELU281612	29 ¹ / ₂ (749mm)	17 ¹ / ₂ (445mm)	28 (711mm)	16 (406mm)	11 ¹ / ₂ (292mm)	See	33 (838mm)
ELUH2816	30 ¹ / ₂ (775mm)	18 ¹ / ₂ (470mm)	28 (711mm)	16 (406mm)	7 ¹ / ₂ (191mm)	Template**	36 (914mm)
ELUH281610	30 ¹ / ₂ (775mm)	18 ¹ / ₂ (470mm)	28 (711mm)	16 (406mm)	10 (254mm)		36 (914mm)
ELUH281612	30 ¹ / ₂ (775mm)	18 ¹ / ₂ (470mm)	28 (711mm)	16 (406mm)	11 ¹ / ₂ (292mm)		36 (914mm)

^{*}Length is left to right. Width is front to back.
**Template is packed with every sink.

