

# SPEAKMAN®

## SE-7000 & SE-7001

### HEAT TRACED COMBINATION SHOWER & EYE/FACE WASH

#### DESCRIPTION

SE-7000 Freeze protected combination shower and eye/face wash units are wrapped with heat trace cable and insulation and jacketed with an easy access ABS shell to protect them to -50°F. Eye/Face wash features dual aerated spray outlets with automatic flow controls and flip top dust covers. The impellar action shower is activated by a high visibility yellow pull rod. An integral freeze valve protects unit from freezing in case of power outage.

#### SPECIFICATIONS

**Showerhead:** 8" Dia. CYCOLAC® yellow plastic

**Flow Control:** Internal 20 gpm regulator

**Freeze Valve:** Activates automatically below 40°F

**Valve:** 1" NPTF chrome plated brass stay-open ball valve

**Activator:** Powder coated high visibility yellow, aluminum triangular pull rod

**Internal Stanchion:** 1" IPS galvanized steel pipe

**Inlet:** SE-7000: 1" NPT male, bottom supply

SE-7001: 1" NPT male, top supply

**Performance:** 20 gpm @ 30 psi

**Finish:** Dura-Jade green ABS plastic

#### EYE/FACE WASH

**Spray Head:** (2) yellow ABS plastic spray outlets with automatic flow control and flip-top dust caps

**Valves:** ½" NPT brass, 3-way chrome plated ball valve

**Performance:** 3.82 gpm @ 30 psi

**Activator:** Stainless steel push handle

#### ELECTRIC

**Heating Tape:** Self-limiting parallel resistance cable with braided metal shield

**Thermostat:** Preset, hermetically sealed single pole contact switch. Temperature range 60° to 70° F

**Insulation:** Closed cell rubber foam

**Junction Box:** NEMA 4 water tight and dust tight, suitable for indoor or outdoor locations

**Power Supply:** 120 vac, 60 cycle, single phase

**Electrical Classification:** Class 1 Division 2 GRP. B, C, D

**Ground Fault Protection:** Installation will require minimum 30 mA GFD

**Compliance:** ANSI Z358.1; Factory mutual approved



#### INTEGRAL OPTIONS

- DH Drench hose
- IT Immersion well thermometer
- SPV Scald protection valve
- PL Pilot Light

#### ACCESSORIES

- VPL Area light
- VPL-C1D2 Hazardous area light
- FLW Flow switch
- FLW-DPDT Flow switch - double pull double throw

Job Name _____
Location _____
Architect/Engineer _____
Sales Representative _____
Wholesaler _____
Date _____ Model # _____