SPEAKMAN®

1-800-537-2107 Fax: 1-800-977-2747 www.speakmancompany.com

WATERFALL, SHOWER SYSTEM & VERSATILE[™]



Showerhead & Hand Held GENERAL SPECIFICATION

Flow control device reduces flow to 2.5 gpm/9.46 lpm maximum, to meet existing ANSI A112.18.1 Standard. 1/2" NPT inlet.

□ S-2555

5" diameter solid brass polished chrome plated down pour rain showerhead with a 10" pivoting extension shower arm. 108 individual water streams produce a full body deluge spray pattern. Arm raises or lowers shower over a 20" range. Key included to set adjustment to arm and showerhead.

🗆 VS-1120 🖒

The complete shower system includes the VS-2000 5-jet hand-held shower and no-tangle hose, VS-111 Diverter with easy-pop lift knob, VS-122 Three (3) position wall mounted hand-held shower holder. S-2252 head is not included.

□ VS-1001-ADA 👆

VersatileTM hand held shower features a hand-held shower with white finish, arm mount bracket, vacuum breaker, 5' metal hose, Combination slide bar/grab bar.

□ VS-1001-ADA-PC 🖔

Versatile $^{\rm TM}$ hand held shower features a hand-held shower with chrome finish, arm mount bracket, vacuum breaker, 5' metal hose, Combination slide bar/grab bar.

This space for Architect/Engineer approval.

