SPEAKMAN®

SE-7001

HEAT TRACED COMBINATION SHOWER & EYE/FACE WASH

DESCRIPTION

SE-7001 Freeze protected combination shower and eye/face wash units are wrapped with heat trace cable and insulation and jacketed with an easy access ABS shell to protect them to -50°F. Eye/Face wash features dual aerated spray outlets with automatic flow controls and flip top dust covers. The impellar action shower is activated by a high visibility yellow pull rod. An integral freeze valve protects unit from freezing in case of power outage.

SPECIFICATIONS

Showerhead: 8" Dia. CYCOLAC® yellow plastic

Flow Control: Internal 20 gpm regulator

Freeze Valve: Activates automatically below 40°F

Valve: 1" NPTF chrome plated brass stay-open ball valve

Activator: Powder coated high visibility yellow, aluminum triangular pull rod

Internal Stanchion: 1" IPS galvanized steel pipe

Inlet: 1" NPT male, top supply Performance: 20 gpm @ 30 psi Finish: Dura-Jade green ABS plastic

EYE/FACE WASH

Spray Head: (2) yellow ABS plastic spray outlets with automatic flow control and flip-top dust caps

Valves: 1/2" NPT brass, 3-way chrome plated ball valve

Performance: 3.82 gpm @ 30 psi Activator: Stainless steel push handle

ELECTRIC

Heating Tape: Self-limiting parallel resistance cable with braided metal shield

Thermostat: Preset, hermetically sealed single pole contact switch. Temperature range 60° to 70° F

Insulation: Closed cell rubber foam

Junction Box: NEMA 4 water tight and dust tight, suitable for indoor or outdoor locations

Power Supply: 120 vac, 60 cycle, single phase

Electrical Classification: Class 1 Division 2 GRP. B, C, D

Ground Fault Protection: Installation will require minimum 30 mA GFPD

Compliance: ANSI Z358.1 INTEGRAL OPTIONS

⅃ DH	Drench hose
☐ IT	Immersion well thermometer
□ SPV	Scald protection valve
□ PL	Pilot Light
<u>ACCESSORIES</u>	
☐ VPL	Area light
☐ VPL-C1D2	Hazardous area light
☐ FLW	Flow switch
☐ FLW-DPDT	Flow switch - double pull
	double throw

Job Name	
Location	
Architect/Engineer	
Sales Representative	
Wholesaler	
Date Model #	