

ANYSTREAM® HOTEL

S-2005-H



GENERAL SPECIFICATION

Water conserving pressure compensating Autoflo® device reduces flow to 2.5 GPM/9.46LPM maximum, to meet existing ANSI A112.18.1/CSA B125.1 standard. Brass threaded inlet with ½" NPSM inlet. There is also a dual action combination spray.

□ S-2005-H

Polished chrome plated Anystream® Hotel Showerhead. Spray adjusting T-handle. 2-1/2" face. 5 self-cleaning plunger nozzles resist scale build-up and provide 50 spray streams for a full body coverage pattern. Center core nozzles deliver 8 pulsating-massage jets.

S-2005-HB



□ S-2005-HB

Polished chrome plated Anystream® Hotel Showerhead. Spray adjusting T-handle. 5 self-cleaning plunger nozzles resist scale build-up and provide 50 spray streams for a full body coverage pattern. Center core nozzles deliver 8 pulsating-massage jets.

□ S-2005-HS

Polished chrome plated Anystream® Hotel Showerhead. Spray adjusting T-handle. 5 self-cleaning plunger nozzles resist scale build-up and provide 50 spray streams for a full body coverage pattern. Center core nozzles deliver 8 pulsating-massage jets.

S-2005-HS



OPTIONS

SUFFIX	DESCRIPTION
□ E2	2.0 GPM flow rate (polished chrome finish only, not available on S-2005-HS)
□ PB	Polished brass (S-2005-HB only)
□ BN	Brushed nickel finish (S-2005-H & S-2005-HB only)
□ BP	Blister pack packaging
□ BC	Brushed chrome finish (S-2005-HB only)

This space for Architect/Engineer approval.

