STERLING.

Features

- Compression molded from our exclusive solid Vikrell_® material
- Above-floor-drain (AFD) rough-in
- Factory installed injection molded apron extension and undersupport structure
- Tongue-and-groove 4-piece modular design allows for easy "snap together" installation
- Durable high-gloss finish
- 10-year consumer/3-year commercial limited warranty
- Installation with wall surrounds is the only recommended installation
- 17-1/4" (43.8 cm) bath depth (floor to top of threshold)
- 60-1/4" (153 cm) x 31-1/2" (80 cm) x 75-3/4" (192.4 cm) complete unit rough-in dimensions include flange
- 60" (152.4 cm) x 30" (76.2 cm) x 74-1/4" (188.6 cm) complete unit finished dimensions


Codes/Standards Applicable

Specified model meets or exceeds the following:

- ASTM E162
- ASTM E662
- CSA B45.5/IAPMO Z124



SURROUND



60" (152.4 cm) AFD BATH AND WALL

Colors/Finishes

- 0: White
- Other: Refer to Price Book for additional colors/finishes

Specified Model

Model	Complete Unit Description	Colors/Fi	Colors/Finishes	
71090112	60" (152.4 cm) AFD bath and wall surround, left drain	0 🗆	Other	
71090122	60" (152.4 cm) AFD bath and wall surround, right drain			
Model	Component Description	Colors/Finishes		
71091112	60" (152.4 cm) AFD bath only, left drain	0 🗆	Other	
71091122	60" (152.4 cm) AFD bath only, right drain	0	□ Other	
Model	Wall Component Description	Colors/Fi	Colors/Finishes	
71094100	Complete wall set	0	Other	
Model	ADA Adaptive Component Description	Colors/Fi	Colors/Finishes	
71090118	ADA complete unit with Age-in-Place backers, left drain	0 🗆	Other	
71090128	ADA complete unit with Age-in-Place backers, right drain	0	Other	

АССТАІМти

7109011

ALSO 71090122

АССЬАІМтм

Technical Information

Fixture*:						
Basin area:						
Bathing wel	I	42" (106.7 cm) x 16-1/4" (41.3 cm)				
Top area		56" (142.2 cm) x 23-3/4" (60.3 cm)				
To overflow:						
Water depth		12" (30.5 cm)				
Capacity		34 gal (128.7 L)				
* Approximate measurements for comparison only.						
Model	doc wid	or maximum th	door maximum height			
71090112 58- 71090122		1/2" (148.6 cm)	56-1/2" (143.5 cm)			
* Varies with alternative walls.						

Installation Notes

Install this product according to the installation guide.

Size the drain hole clearance to fit the drain assembly that will be used.

End stud positioning is critical if apron nailing-in flanges are to be used.

Studs should be positioned roughly as shown.

Adjacent finished wall thickness must not exceed 9/16'' (1.4 cm).

